




BA systems
22 Bidwell Road
Rackheath Industrial Estate
Norwich NR13 6PT

call 01603 722330
fax 01603 722777
email sales@basystems.co.uk
web www.basystems.co.uk



NBS Specifications

Typical NBS L30 Specifications

1. Wall Mounted Handrails

Manufacturer: BA Systems, 22 Bidwell Road, Rackheath Industrial Estate, Norwich, NR13 6PT

Tel: 01603 722330; sales@basystems.co.uk; www.basystems.co.uk

Product Reference: Vetobac VBA99 Wall Mounted Handrails 42mm diameter

Internal/ External: Internal/ External

Guarding: None

Infill: None

Fixing Methods: Wall brackets with cover rose in non touch stainless steel.

Design Criteria: Touch handrails in VBA99 with test certification of efficacy in destroying Covid 19 virus.

Other Requirements: Load requirement 0.74kN/m; Handrails to be mounted between 900mm and 1000mm above finished floor level or the pitch line of the stairs; Handrails to extend 300mm beyond the top and bottom nose of the stairs.

2. Floor Mounted Handrails and Balustrades

Manufacturer: BA Systems, 22 Bidwell Road, Rackheath Industrial Estate, Norwich, NR13 6PT

Tel: 01603 722330; sales@basystems.co.uk; www.basystems.co.uk

Product Reference: Vetobac VBA99 Wall Mounted Handrails with B20 Balustrade System

Internal/ External: Internal/ External

Guarding: 50mm diameter satin stainless steel non touch posts

Infill: 11.5mm thick clear toughened and laminated and heat soak tested glass

Fixing Methods: To be determined face mounted to surface mounted

Design Criteria: Touch handrails in VBA99 with test certification of efficacy in destroying Covid 19 virus, mounted to balustrade

Other Requirements: Load requirement 0.74kN/m, 1.5kN/m, 3.0kN/m; Handrails to be mounted between 900mm and 1000mm above finished floor level or the pitch line of the stairs; Handrails to extend 300mm beyond the top and bottom nose of the stairs.